Approved For Helease 2002/06/14 CIA RDF78B04767A000400050010-0 on 6 May 1

to assist in preparing a prafact for 74 on 6 May 1

of Mission Concerning Lispectral acquisition

and bi color viruing are exposed in the bi-spectral

mode of acquisition. Bi-spectral coverage refers to a technique

of acquiring conjugate imagery with two cameras each using a filter which has its peak transmission near opposite ends of the visible spectrum. In this case, a red filter was used on the fwd camera and a green on the aft. In acquiring photography in this manner, the density of images on the black and white records is related to the filters through which they were exposed.

25X1

25X1

To exploit the advantages of bi-spectral photography, the two balck and white records can be analyzed individually with respect to the colors which the density represents. I.E., objects on the fwd (red filter) record which appear relatively light (low density) on the DP compared to the same image on the aft (green filter) record can be assumed to be reflecting in the red end of the spectrum. However, these conclusions cannot be accepted as absolute. The angle of the sun relative to the taking lens, atmospheric attenuation, exposure, and reproduction characteristics must also be considered. Even under optimum conditions, the color of an object can only be established as being warm (red or near red) or cool (green or toward the blue end of the spectrum).

In order to facilitate the readout of bi-spectral information, the photography can be viewed in a color mode referred to as "bicolor". Bicolor is a psuedo color generated from two colors of

Approved For Release 2002/06/17 : TOR-REFERENT/767A000400050010-0

the spectrum instead of the three, as is necessary for "natural" color. In order to create bicolor imagery, the black and white (DP) records from both cameras (ferward and aft panoramic) are projected onto a common surface, in register, through filters comparable to those used in the taking situation (fwd through red - aft through green). Information available by this technique will be similar in scope and value to that gained from the bispectral records viewed independently. However, the bispectral information becomes more readily apparent and a faster readout is possible. Red or warm tones will appear red or some variation thereof; green or cool tones will appear predominantly green.

The problem of employing the bicolor method of exploitation is that the images must be appropriately filtered and projected in register. The geometry of the KH-4B/is such that the imagery must be rectified in order to be successfully registered over areas larger than approximately 0.1 x 0.1 mm.

> NEXT : ct currently prepared to produce color prints from the bi-spectral imagery on a production basis for the Community.

the ARES, available the center is note.

WIRKING Reved For Release 2002 SECREP 78B04767A000400050010-0

Bi Color

25X1

25X1

Several passes of Mission were exposed in the bi-color or bi-spectral mode of acquisition. Bi-color refers to a technique of acquiring stereo photography with two cameras using filters having peak transmission near opposite ends of the visable spectrum. In this case, a red filter on the fwd camera and a green on the aft. In acquiring photography in this manner, the density of the black and white records is related to the filters through which they were exposed.

To exploit the advantages of bi-spectral (bi-scolor) photography, the two black and white records can be analyzed individually with respect to the colors which the density represents. I.E., objects on the fwd (red filter) record which appear relatively light (low density) on the DP compared to the same image on the aft (green filter) record can be assumed to be reflecting in the red end of the spectrum. However, these conclusions cannot be accepted as absolute. The angle of the sun relative to the taking lens, atmospheric attenuation, exposure, and reproduction characteristics must also be considered. Even under optimum conditions, the color of an object can only be established as being warm (red or near red) or cool (green or toward the blue end of the spectrum).

In order to facilitate the readout of bi-spectral information, the photography can be viewed via the bi-color technique. Bi-color is a psuedo color generated from two colors of the spectrum instead

TOP SECILI 100 SECILI

of the normal three. In order to generate bi-color imagery, the black and white (DP) records from both cameras are projected on to a common surface, in register, through filters comparable to those used in the taking situation (fwd through red-aft through green). Information sained by this technique will be similar in scope and value to that gained from the bi-spectral records viewed independently. However, the bi-spectral information becomes more readily apparent and a faster readout is possible. Red or warm tones will appear readous or some variation thereof; green or cool tones will appear as such.

The problem of Employing the bi-color method of exploitation is that the records must be appropriately filtered and projected in register. The geometry of the KH-4B is such that the imagery must be rectified in order to be successfully registered.

into bi- spectral aspects of images in cloud or terrain

25X1

Bi Color

Several passes of Mission were exposed in the bi-color bi-spectral mode of acquisition. Bi color refers to a technique of acquiring the photography with two cameras using of filters having peak transmission near opposite ends of the visable spectrum. In this case, a red filter on the fwd camera and a green on the aft. In acquiring photography in this manner, the density of the black and white records is related to the filters through which they were exposed.

To exploit the advantages of bi-spectral (bi-color) photography, the two black and white records can be analyzed individually with respect to the colors which the density represents. I.E., objects on the fwd (red filter) record which appear relatively light (low density) on the DP compared to the same image on the aft (green filter) record can be assumed to be reflecting in the red end of the spectrum. However, these conclusions cannot be accepted as absolute. The angle of the sun relative to the taking lens, atmospheric attenuation, exposure, and reproduction characteristics must also be considered. Even under optimum conditions, the color of an object can only be established as being warm (red or near red) or cool (green or toward the blue end of the spectrum).

In order to facilitate the readout of bi-spectral information, the photography can be viewed viewed bi-color technique. Bi-color is a psuedo color generated from two colors of the spectrum instead

IVI STUTET

HUMME PAPER

ILLEGIB

Approved For Release 2002/06/17 : CIA-RDP78B047 of the normal three. In order to genero te bi-color imagery, the black and white (DP) records from both cameras are projected on to a common surface, in register, through filters comparable to those used in the taking situation (fwd through red aft through green). Information gained by this technique will be similar in scope and value to that gained from the bi-spectral records viewed independently . However, the bispectral information becomes more readily apparent and a faster readout is possible. Red or warm tones will appear red or some variation thereof; green or cool tones will appear The problem of employing the bi-color method of exploitation is that the records must be appropriately filtered and projected in register. The geometry of the KH-4B is such that the imagery must be rectified in order to be successfully registered order

ILLEGIB

P78B04767A00040**0**050010-0

25X1

DRAFT 1 May 1968

MEMORANDUM FOR: Deputy Director, NPIC

SUBJECT:

Exploitation of Bicolor Imagery

With the prospect of the next scheduled KH-4 mission being partially (approximately 30 passes) programmed to result in photography with a capability of producing bicolor imagery the following actions will be implemented.

- a. A paragraph will be included in preface of the OAK and OAK

 b, spectral a construction of bicolor and its technical aspects

 for the reconstruction of bicolor imagery. This statement on the

 nature of bicolor is being developed by Technical Services and Support

 Group in coordination with IEG.
- b. The bicolor reconstruction capability of the film covering
 each target will be indicated by the code "BC" in the photo reference
 line immediately following the pass number

The following will be included in the preface to explain the significance of BC in the photo reference line.

"BC (bicolor) indicates that the target is covered on a pass which was programmed for the bi-spectral mode of operation. However, this does not mean that individual targets can be perceived as bicolor since atmospherics, defilade, and other obscurations may degrade the image(s) to the extent that bicolor cannot be reconstructed. Also, reconstruction is possible only with imagery from both cameras."

25X1

Approved For Release 2002/06/17: CIA-RDP78B04767A000400050010-0

•

25X1

25X1

25X1

25X1

Approved For Release 2002/09/77: CHA-RDP78B04767A000490050010-0

Note:

The above statement on the explanation of the code "BC" is still subject to further refinement.